



**Hewlett Packard**  
Enterprise

# **HPE Connected Backup**

Software Version: 8.8.7

## Data Center Disaster Recovery

Document Release Date: July 2017

Software Release Date: July 2017

## Legal Notices

### Warranty

The only warranties for Hewlett Packard Enterprise Development LP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HPE shall not be liable for technical or editorial errors or omissions contained herein.

The information contained herein is subject to change without notice.

### Restricted Rights Legend

Confidential computer software. Valid license from HPE required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

### Copyright Notice

© Copyright 2017 Hewlett Packard Enterprise Development LP

### Trademark Notices

Adobe™ is a trademark of Adobe Systems Incorporated.

Microsoft® and Windows® are U.S. registered trademarks of Microsoft Corporation.

UNIX® is a registered trademark of The Open Group.

This product includes an interface of the 'zlib' general purpose compression library, which is Copyright © 1995-2002 Jean-loup Gailly and Mark Adler.

## Documentation updates

The title page of this document contains the following identifying information:

- Software Version number, which indicates the software version.
- Document Release Date, which changes each time the document is updated.
- Software Release Date, which indicates the release date of this version of the software.

To check for recent software updates, go to <https://softwaresupport.hpe.com/patches>.

To verify that you are using the most recent edition of a document, go to <https://softwaresupport.hpe.com/manuals>.

This site requires that you register for an HPE Passport and sign in. To register for an HPE Passport ID, go to <https://hpp12.passport.hpe.com/hppcf/login.do>.

You will also receive updated or new editions if you subscribe to the appropriate product support service. Contact your HPE sales representative for details.

## Support

Visit the HPE Software Support Online web site at <https://softwaresupport.hpe.com>.

This web site provides contact information and details about the products, services, and support that HPE Software offers.

HPE Software online support provides customer self-solve capabilities. It provides a fast and efficient way to access interactive technical support tools needed to manage your business. As a valued support customer, you can benefit by using the support web site to:

- Search for knowledge documents of interest
- Submit and track support cases and enhancement requests
- Download software patches
- Access product documentation
- Manage support contracts

- Look up HPE support contacts
- Review information about available services
- Enter into discussions with other software customers
- Research and register for software training

Most of the support areas require that you register as an HPE Passport user and sign in. Many also require a support contract.

To register for an HPE Passport ID, go to <https://hpp12.passport.hpe.com/hppcf/login.do>.

To find more information about access levels, go to <https://softwaresupport.hpe.com/web/softwaresupport/access-levels>.

## **About this PDF version of online Help**

This document is a PDF version of the online Help.

This PDF file is provided so you can easily print multiple topics or read the online Help.

Because this content was originally created to be viewed as online help in a web browser, some topics may not be formatted properly. Some interactive topics may not be present in this PDF version. Those topics can be successfully printed from within the online Help.

# Contents

Chapter 1: Before You Begin .....	7
Scenarios Not Addressed by the Disaster Recovery Guide .....	7
Required Disaster Recovery Items .....	7
Registry and Directory SQL database backups .....	7
License.dat file .....	8
Configuration\$ folder .....	8
Windows Registry Connected\Keys .....	8
Security files .....	8
Additional Components .....	9
Chapter 2: Recovering a Standalone Data Center .....	11
Recover a Standalone Data Center .....	11
Tasks .....	11
Install and Configure Microsoft Windows .....	11
Install and Configure SQL Server .....	11
Recover the Connected Databases .....	12
Install the Data Center Software .....	13
Data Center Verifications .....	13
Chapter 3: Recovery of a Mirrored Data Center .....	15
Recover One Data Center Server of a Mirrored Pair .....	15
Tasks .....	15
Install and Configure Microsoft Windows .....	15
Install and Configure SQL Server .....	16
Recover the Connected Databases .....	16
Install the Data Center Software .....	17
Recover Archives from the Functional Server .....	18
Find and Remove Orphaned Archives .....	19
Verify the Data Center Recovery .....	19
Recover Both Servers of a Mirrored Data Center .....	20
Tasks .....	20
Install and Configure Microsoft Windows .....	21
Install and Configure SQL Server .....	21
Recover the Connected Databases .....	21
Install the Data Center Software .....	22
Verify the Data Center Recovery .....	23
Recover the Secondary Server .....	23
Chapter 4: Recovering a Clustered Data Center .....	24

- Recover a Clustered Data Center Server ..... 24
  - Tasks ..... 24
  - Install and Configure Microsoft Windows ..... 24
  - Install and Configure SQL Server ..... 25
  - Recover Databases to a Data Center Server ..... 25
  - Install the Data Center Software ..... 26
  - Change the Volume IDs for Archives ..... 27
  - Find and Remove Orphaned Archives ..... 27
  - Verify the Data Center Recovery ..... 28
- Recover a Mirrored Pair from a Clustered Data Center ..... 29
  - Tasks ..... 29
  - Restrictions ..... 29
  - Recover the Archives After a Disaster ..... 30
- Recover a Non-Mirrored Clustered Data Center ..... 30
  - Tasks ..... 30
  - Restrictions ..... 31
  - Install and Configure Microsoft Windows ..... 31
  - Install and Configure SQL Server ..... 31
  - Recover the Connected Databases ..... 31
  - Install the Data Center Software ..... 33
  - Data Center Verifications ..... 33
- Send documentation feedback ..... 35



# Chapter 1: Before You Begin

This chapter contains information that you need before you start the disaster recovery process. If you have questions about the information in this chapter, contact Support.

- [Scenarios Not Addressed by the Disaster Recovery Guide, below](#)
- [Required Disaster Recovery Items, below](#)
- [Additional Components, on page 9](#)

## Scenarios Not Addressed by the Disaster Recovery Guide

Do not attempt to perform the procedures in this document under any of the following conditions:

- You run a standalone Data Center and you have lost any archives or volumes.
- You run a mirrored or clustered Data Center and you have lost archives or volumes on both sides of the affected server pair.
- You run a mirrored or clustered Data Center, you have lost both sides of the server, and you do not have good backups for either side of your Data Center.
- You run a non-mirrored clustered Data Center and you have lost archives or volumes on the Registry Master Server or Directory Server.

If any of these scenarios exist, contact Support.

## Required Disaster Recovery Items

The items in this section are required for any disaster recovery process. Be sure that these items are saved to a secure backup location on a regular basis as a part of your Data Center maintenance

### Registry and Directory SQL database backups

This can be either the .bak backup files, or the .mdf and .ldf files themselves.

#### To back up Registry and Directory databases on a standalone Data Center

1. Open the Scheduled Tasks Control Panel.
2. Right-click **WeeklyMaint**, and then select **Run**.
3. Close the Scheduled Tasks Control Panel.

#### To back up Registry and Directory databases on a mirrored or clustered Data Center

**NOTE:**

Mirrored Data Center servers have both a Directory and Registry database.

Clustered Data Center servers can have both a Directory and Registry database (non-dedicated Registration Master), just a Registry database (dedicated Registration Master), or just a Directory database (directory server).

1. Open the SQL Server Management Studio, and then connect to the Data Center.
2. Run `\DataCenter\DRProcs\database_backup.sql`.
3. Close the SQL Server Management Studio.

## License.dat file

Each server has a `License.dat` file specific to its Network Identification Card (NIC). The license file is in the Data Center installation folder. To request a new license, use the License Request form on the Big Data Download Center. To access the Big Data Download Center, go to

<https://downloads.autonomy.com>

## Configuration\$ folder

In the `\DataCenter` folder on the Data Center, copy the `Configuration$` folder to a safe location. This folder contains the Connected Backup Agent file sets and configuration files. Directory servers in a clustered configuration do not have a `Configuration$` folder, and do not require this item for disaster recovery.

## Windows Registry Connected\Keys

Export the Windows registry key from the Data Center server to a folder in a safe location. The key is in the following registry location:

**HKEY\_LOCAL\_MACHINE\SOFTWARE\Wow6432Node\Connected\Keys**

### To export the Keys registry key

1. Open the Registry Editor on your Data Center server.
2. Locate the `...\Connected\Keys` key, and then examine the values.
3. If the MEK and PMEK keys and values are not visible to you, right-click `...\Connected\Keys` and then select **Permissions**. Change the permissions for the logged-on user to **Read**. To close the window, click **OK**.
4. After the MEK and PMEK keys are visible, right-click `...\Connected\Keys`, and then select **Export**.
5. Navigate to a folder in a safe, known location, provide a file name for the export file, and then click **Save**.
6. The exported file has a `.reg` extension and contains the key that is required to recover your Data Center.
7. Close the Registry Editor.

## Security files

In the `\DataCenter` folder on the Data Center, back up the following files:

- `PrivateKey.pem`
- `Certificate.pem`
- `dh1024.pem`

## Additional Components

Be sure to have the following components available during the Disaster Recovery process:

- ***Installing the Data Center guide***  
Provides information on installation procedures for Microsoft Windows and SQL Server
- **Connected Backup Requirements Matrix**  
Provides information on supported hardware for Connected Backup Data Center installations.
- ***Connected Backup Interoperability Matrix***  
Identifies third-party software that works with Connected Backup software.
- **Microsoft Windows Server software**  
Use the same software version that you installed on the Data Center server before the disaster. If you run a mirrored server configuration, you must install the same software version on each server pair.
- **Microsoft SQL Server software**  
Use the same software version that you installed on the Data Center server before the disaster. If you run a mirrored server configuration, you must install the same software version on each server pair.
- **Data Center software**  
Use the same software version that you installed on the Data Center server before the disaster. If you run a mirrored server configuration, you must install the same software version on each server pair.
- **SQL scripts**  
Many disaster recovery procedures in this guide contain SQL scripts that you must download to complete the disaster recovery tasks. These scripts are in the Data Center installation folders `\DataCenter\DRProcs` and `\DataCenter\Scripts`.
- **Windows domain account and password used by Data Center services**  
The following are the three service accounts:
  - CNTD\_DCServices
  - CNTD\_WebServices
  - CNTD\_DataBundler

If you run a mirrored Data Center configuration, use the same Windows domain account and password on each server.
- **Latest version device drivers for server hardware**  
Collect the most recent drivers according to vendor recommendations.
- **Vendor contact information**  
Collect this information for all hardware, software, and firmware in your Data Center
- **Data Center Management Console (DCMC)**  
Available after you install the Data Center software.

- **Archives**

You must have access to all archives for the Data Center configuration.

# Chapter 2: Recovering a Standalone Data Center

This chapter describes how to recover a standalone Data Center.

- [Recover a Standalone Data Center, below](#)

## Recover a Standalone Data Center

This section describes how to recover your standalone Data Center.

### Tasks

To restore a standalone Data Center, perform the following tasks in the order that they are presented:

**NOTE:**

You must complete the following tasks in order. If you have already completed tasks during your recovery, continue with the task that contains the next steps for the disaster recovery.

1. Before you perform the procedures in this manual, ensure you have the required files and information for the disaster recovery. See [Before You Begin, on page 7](#).
2. Install the Microsoft Windows Server operating system. See [Install and Configure Microsoft Windows, below](#).
3. Install Microsoft SQL Server. See [Install and Configure SQL Server, below](#).
4. Restore the SQL databases. See [Recover the Connected Databases, on the next page](#)
5. Install the Data Center software. See [Install the Data Center Software, on page 13](#).
6. Verify that the procedures have restored your Data Center components. See [Data Center Verifications, on page 13](#).

## Install and Configure Microsoft Windows

To install the Microsoft Server operating system, use the following guidelines:

- Use the same software version that you installed on the Data Center server before the disaster.
- For information about how to install the Microsoft Server operating system, refer to Chapter 2: Preparing for Installation in the *Installing the Data Center* guide.
- For information about Data Center hardware and software requirements, refer to the *Connected Backup Requirements Matrix* guide.

## Install and Configure SQL Server

To install SQL Server, use the following guidelines:

- Use the same software version that you installed on the Data Center server before the disaster.
- Use the same domain account that you previously used for your Data Center installation.

**CAUTION:**

Ensure that the Data Center installation account has local administrator privileges and SQL Server sa account rights.

If you attempt a Data Center recovery with an account that does not have SQL Server sa account rights, you will have to reinstall SQL Server and restart the Data Center recovery.

- For information about how to install SQL Server, refer to the Chapter 2: Preparing for Installation in the *Installing the Data Center* guide.

## Recover the Connected Databases

If the Data Center databases have been lost or corrupted during the server disaster, use the following procedure to restore the Registry and Directory databases to the Data Center server. Perform this task on each database that you need to restore.

### To restore the databases

1. From your backup, copy the .bak or .mdf and the .ldf files to the same folder location on the Data Center in recovery as was on the original Data Center.
2. Open the SQL Server Management Studio and then connect to the Data Center server in recovery.
3. If you restore databases from a backup (.bak files)
  - a. Right-click **Databases**, and then click **Restore Database**.
  - b. Type the name of the database to restore in **To database**.
  - c. Select **From device**, and then click the ellipsis button (...).
  - d. Ensure that **File** is selected for **Backup Media**, and then click **Add**.
  - e. Navigate to the location of the .bak file and select the file. Click **OK**.
  - f. To start the database restore process, click **OK**.  
You have restored the selected database. Repeat this step for each database you need to restore.
4. If you restore databases from backed up .mdf and .ldf files
  - a. Right-click **Databases** and then click **Attach**. The Attach Databases dialog box opens.
  - b. Click **Add** to select a database. The Locate Database Files dialog box opens.
  - c. Navigate to the location of the database and select the appropriate .mdf file.
  - d. Click **OK** to accept the database selection.
  - e. If the location of the .ldf file is in a different folder, click the ellipsis button (...) in the database details section for the .ldf file for the database, and then select the appropriate .ldf file.
  - f. Click **OK**.  
You have attached the selected database. Repeat this step for each database that you need to attach.
  - g. Verify that this procedure restored your databases.  
You cannot verify that the information in the database is correct and accounted for, but you can verify that the tables exist and contain appropriate information. To ensure the tables exist and contain the appropriate information, run the following queries, and then verify that each query displays information.

```
PRINT 'Number of active accounts on server'  
SELECT COUNT(*) FROM Registry.dbo.Customer  
WHERE Status = 'A'  
PRINT 'Number of ArchiveSet rows on server'  
SELECT COUNT(*) FROM Directory.dbo.ArchiveSet
```

The results of the first query returns the number of active accounts in your SQL database. If that number does not match the number of active accounts that you believe are in your SQL database, contact Support.

## Install the Data Center Software

Use the following procedure to install the Data Center software on a Connected Backup Data Center server that was lost or corrupted.

### To install the Data Center Software after a disaster

1. From your backup, copy the .reg file that you created in [Before You Begin, on page 7](#) to the Data Center in recovery, and then run the file to import the Master Encryption Keys (MEK and PMEK).
2. Install the Connected Backup Data Center software as a **Standalone server**. For more information, refer to the *Installing the Data Center* guide.
3. Open the Data Center Management Console (DCMC), and then stop all Data Center services.
4. From your backup, copy the following files to \DataCenter:
  - PrivateKey.pem
  - Certificate.pem
  - dh1024.pem
  - License.dat
5. From your backup, copy the Configuration\$ folder to \DataCenter.
6. From your backup of the Configuration\$ folder, copy the cafile.pem file to the DataCenter\ folder.
7. Use the DCMC to restart Data Center services.  
You have installed the Data Center software.

## Data Center Verifications

### To verify that you have recovered the Data Center

1. To verify that the Support Center works, log on and search for any number of accounts.
2. To verify that Account Management Website works, log on and view account information (if applicable).

You might be unable to account for some database processes because they might happen after the database backup occurs, but before the actual disaster. The following list includes some items that might not appear in the database:

- Accounts registered after the last backup
- Backups for current accounts
- Changes made to account status
- New Support Center technicians created
- Support Center technician password changed

# Chapter 3: Recovery of a Mirrored Data Center

This chapter describes how to recover a mirrored Data Center.

- [Recover One Data Center Server of a Mirrored Pair, below](#)
- [Recover Both Servers of a Mirrored Data Center, on page 20](#)

## Recover One Data Center Server of a Mirrored Pair

This section describes how to recover one Data Center server of a mirrored pair while the other Data Center server in the pair continues to be functional.

### Tasks

To recover one Data Center server of a mirrored pair, complete the following tasks:

**NOTE:**

You must complete the following tasks in order. If you have already completed tasks during your recovery, continue with the task that contains the next steps for the disaster recovery.

1. Before you perform the procedures in this manual, make sure you have the required files and information for the disaster recovery. See [Before You Begin, on page 7](#).
2. Install the operating system. See [Install and Configure Microsoft Windows, below](#)
3. Install SQL Server. See [Install and Configure SQL Server, on the next page](#)
4. Install the Data Center software. See [Install the Data Center Software, on page 17](#).
5. Restore the SQL databases. See [Recover the Connected Databases, on the next page](#).
6. Recover the archives. See [Recover Archives from the Functional Server, on page 18](#).
7. Find and remove orphaned archives. See [Find and Remove Orphaned Archives, on page 19](#).
8. Verify the success of the recovery. See [Verify the Data Center Recovery, on page 19](#).

## Install and Configure Microsoft Windows

**To install the Microsoft Server operating system, use the following guidelines:**

- Use the same software version that you installed on the Data Center server before the disaster.
- For information about how to install the Microsoft Server operating system, refer to Chapter 2: Preparing for Installation in the *Installing the Data Center* guide.
- For information about Data Center hardware and software requirements, refer to the *Connected Backup Requirements Matrix* guide.

## Install and Configure SQL Server

To install SQL Server, use the following guidelines:

- Use the same software version that you installed on the Data Center server before the disaster.
- Use the same domain account that you previously used for your Data Center installation.

**CAUTION:**

Ensure that the Data Center installation account has local administrator privileges and SQL Server sa account rights.

If you attempt a Data Center recovery with an account that does not have SQL Server sa account rights, you will have to reinstall SQL Server and restart the Data Center recover

- For information about how to install SQL Server, refer to Chapter 2: Preparing for Installation in the *Installing the Data Center* guide.

## Recover the Connected Databases

This section explains how to restore the Data Center databases to a mirrored Data Center server after a database loss on the recovering server. This procedure lets backups and restorations continue on the functional server.

**To restore your databases from a working Data Center server in a mirror to the Data Center server in recovery**

1. On the functional server, use the DCMC to stop the ReplicationServer and Compactor services.
2. On both servers, use the Services Control Panel to verify that SQLServerAgent and MSSQLServer are both running.
3. On the functional server, open the SQL Server Management Studio and then connect to the functional server.
4. On the functional server create a full database backup on disk of both the Directory and the Registry database files. To do so, run database\_backup.sql in \Data Center \Scripts.
5. Copy the following files from the functional server to the server in recovery:
  - Directory.bak
  - Registry.bak

By default, these files are located in \Program Files\Microsoft SQL Server\MSSQL\Backup on the designated SQL database volume. You select this volume during the Data Center Setup process.

6. On the server in recovery, use the Services Control Panel to stop the SQL Server and SQL Server Agent services. Then, restart the SQL Server and SQL Server Agent services (in that order).
7. On the server in recovery, open the SQL Server Management Studio and then connect to the server in recovery
8. On the server in recovery, run the database\_recovery.sql script from \Data Center\DRProcs on the functional server to restore the database backups.

If the backup and database files are not in the default locations, using Notepad, edit the `database_recovery.sql` script to replace `\Program Files\Microsoft SQL Server\MSSQL` with the correct location of the backup and database files.

9. Make sure that your SQL service account has read access to any volumes that contain the Customer archives.
10. On the server in recovery, run the `FilesInCustomersFolder.sql` script from `\DataCenter\DRProcs` on the functional server.
11. Run the following query:  

```
exec Directory..sp_UpdateVolumeID
```

This process consumes more time and does not display any status.
12. On both servers, to verify that you recovered the databases correctly, run the following queries:  

```
SELECT COUNT(*) 'Customer Rows' FROM Registry.dbo.Customer  
SELECT COUNT(*) 'Community Rows' FROM Registry.dbo.Community  
SELECT COUNT(*) 'ArchiveSet Rows' FROM Directory.dbo.ArchiveSet  
SELECT COUNT(*) 'Symlink Rows' FROM Directory.dbo.Symlink
```

All counts should be equal or close to equal on both sides of the mirrored pair.  
These queries let you verify that the tables exist and contain appropriate information.
13. On both servers, close SQL Server Management Studio.
14. On the functional server, use the DCMC to restart the `ReplicationServer` and `Compactor` services.

## Install the Data Center Software

This section describes how to install the Data Center software on a Data Center server where data was lost or corrupted because of a disaster.

### To install the Data Center Software after a disaster

1. From your backup, copy the `.reg` file that you created in [Before You Begin, on page 7](#) to the Data Center in recovery, and then run the file to import the Master Encryption Keys (MEK and PMEK).
2. Install the Connected Backup Data Center software in the same role that you initially installed it.
  - If your server in recovery was the primary server in the mirror, install the Data Center software as the **Primary server in a new cluster**.
  - If your server in recovery was the secondary server, install the Data Center software as the **Secondary server**.

Use the same Server ID and Server Group ID values that were in use before the disaster. For more information, see the *Installing the Data Center* guide.

3. On the server in recovery, open the DCMC, and then stop all Data Center services.
4. From your backup, copy the following files to `\DataCenter`:
  - `PrivateKey.pem`
  - `Certificate.pem`

- dh1024.pem
  - License.dat
5. From your backup, copy the Configuration\$ folder to \DataCenter.
  6. From your backup of the Configuration\$ folder, copy the cafile.pem file to the DataCenter\ folder.
  7. On the server in recovery, use the DCMC to re-start all Data Center services.  
You have installed the Data Center software.

## Recover Archives from the Functional Server

Use this procedure to copy archives from a functional Data Center server to its mirrored Data Center server that lost archives.

### NOTE:

Depending on the number of archives lost, this procedure can take hours or days to complete.

Begin this procedure after you ensure that the affected disk volumes on the server in recovery are replaced or stable. When you replace a lost volume, be sure to replace the volume with another volume of equal or greater capacity.

### To recover archives on volumes that were lost on one side of a mirrored Data Center but still exist on the functional Data Center server

1. On the server in recovery, run the DataCopier tool in the \DataCenter folder.  
The DataCopier - Select Option window opens.
2. Select **Recover a volume**, and then click **Next**.  
The DataCopier - Select Volume window opens.
3. Select the volume you want to recover, and then click **Next**.  
The DataCopier - Summary window opens
4. Click **Next**, and then click **Start**.  
The time required for the recovery process to complete for all the archives that you need to recover can take hours or days. It is important to monitor the status of the archive recovery process.
5. To monitor the progress of the archive recovery
  - a. Open the DataCopier Status window.
  - b. To view the DataCopier log, click **Show Log**.
  - c. To refresh the log, close the file and then click **Show Log** again.If DataCopier could not recover certain archives, Compactor removes the references to the missing archives and then sends a notification to the accounts to back up another copy of the file. Therefore, it is important to run Compactor service after the recovery process completes.
6. Compact any accounts that have a large number of missing archives.
7. On the server in recovery, use the DCMC to make sure that backups and restores are allowed.  
For more information about how to view the backup and restore status of the BackupServer service, see DCMC Help.

## Find and Remove Orphaned Archives

Restoring the databases might leave some newly backed up archives orphaned on the Data Center server.

When an Agent performs a backup that puts archives on the Data Center, the Data Center tracks these files in the Directory database. If an Agent sends archives to the Data Center after the last good backup of the Directory database, the restored database no longer has information about the archives. This creates orphaned archives.

### To find orphaned archives on a Data Center server and remove them

1. On the server in recovery, use the DCMC to stop all Data Center services.
2. On the server in recovery, open the SQL Server Management Studio, and then connect to the server in recovery. Make sure you use an account with administrative privileges. You cannot perform this procedure remotely using SQL Server Management Studio.
3. Run the `FilesInCustomersFolder.sql` script from `\DataCenter\DRProcs`.
4. Make sure that no errors occurred. If you see errors in the script results, contact Support.
5. Run the following query:

```
EXEC Directory..sp_ListUnregisteredFilesInCustomersFolder 'C:\Archives_Orphaned\RemoveFiles.txt'
```

This command creates a text file that lists archives and files that are on disk, but not indexed in the database. This process consumes more time and does not display any status.

6. Review the text file for accuracy. If you are unsure the status of a file, copy the file to a new location or remove the entry from the list.

**NOTE:**

If there are large number of files listed, contact Support.

7. After you review the file, rename `RemoveFiles.txt` as `RemoveFiles.bat`.
8. Use Windows Explorer or the Command Prompt window to run `RemoveFiles.bat` to delete the referenced files from the Data Center.
9. In SQL Server Management Studio, enter the following command:  

```
EXEC Directory..sp_FilesInCustomersFolderCleanup
```

This command removes the database items that the stored procedures in this process created and used.
10. On the server in recovery, close the SQL Server Management Studio.
11. On the server in recovery, use the DCMC to restart all Data Center services.

## Verify the Data Center Recovery

### To verify recovery of the Data Center

1. To verify that the Support Center works, log on and search for a number of accounts.
2. To verify that Account Management Website works, log on and view account information (if applicable).

Some database processes might take place after the database backup but before the actual disaster, which are no longer accounted for in the database. The following is a partial list of items that might not appear in the database:

- Accounts registered during that time
- Backups for current accounts
- Changes made to account status
- New Support Center technicians created
- Support Center technician password changed

## Recover Both Servers of a Mirrored Data Center

If you need to recover both servers in a mirrored Data Center from a disaster, use the procedures listed below to recover the primary server, and then recover the secondary server using the procedures earlier in the chapter.

This section assumes that you have good and recent database backups available, and that all archives still exist on at least one of the Data Centers.

**NOTE:**

You must regularly back up your Connected databases manually for mirrored Data Centers. If you do not have a recent backup of your Connected databases, contact Support.

## Tasks

Complete the following tasks on the primary server of the mirrored pair in recovery:

**NOTE:**

You must complete the following tasks in order. If you have already completed tasks during your recovery, continue with the task that contains the next steps for the disaster recovery.

1. Before you perform the procedures in this manual, make sure you have the required files and information for the disaster recovery. See [Before You Begin, on page 7](#).
2. Install the operating system. See [Install and Configure Microsoft Windows, on the next page](#)
3. Install SQL Server. See [Install and Configure SQL Server, on the next page](#).
4. Install the Data Center software. See [Install the Data Center Software, on page 22](#).
5. Restore the SQL databases. See [Recover the Connected Databases, on the next page](#).
6. Verify the Data Center recovery. See [Verify the Data Center Recovery, on page 23](#).
7. Recover the secondary server in the mirrored pair. See [Recover the Secondary Server, on page 23](#).

## Install and Configure Microsoft Windows

To install the Microsoft Server operating system, use the following guidelines:

- Use the same software version that you installed on the Data Center server before the disaster.
- For information about how to install the Microsoft Server operating system, refer to the Installing and configuring Microsoft software section in the *Installing the Data Center* guide.
- For information about Data Center hardware and software requirements, refer to the *Connected Backup Requirements Matrix* guide.

## Install and Configure SQL Server

To install SQL Server, use the following guidelines:

- Use the same software version that you installed on the Data Center server before the disaster.
- Use the same domain account that you previously used for your Data Center that has the same local administrator privileges for SQL Server to run.
- For information about how to install SQL Server, refer to the Installing and configuring Microsoft software section in the *Installing the Data Center* guide.

## Recover the Connected Databases

If the Data Center databases have been lost or corrupted during the server disaster, use the following procedure to restore the Registry and Directory databases to the Data Center server. Perform this task on each database that you need to restore.

To restore the databases

1. From your backup, copy the .bak or .mdf and .ldf files to the same folder location on the Data Center in recovery as was on the original Data Center.
2. On the server in recovery, open the SQL Server Management Studio and then connect to the Data Center server in recovery.
3. If you restore databases from a backup (.bak files)
  - a. Right-click **Databases** and then click **Restore Database**.
  - b. Type the name of the database to restore in **To database**.
  - c. Select **From device**, and then click the ellipsis button (...).
  - d. Make sure that **File** is selected for **Backup Media**, and then click **Add**.
  - e. Navigate to the location of the .bak file and select the file. Click **OK**.
  - f. To start the database restore process, click **OK**.

You have restored the selected database. Repeat this step for each database you need to restore.
4. If you restore databases from backed up .mdf and .ldf files
  - a. Right-click **Databases** and then click **Attach**.
  - b. In the Attach Databases dialog box, click **Add** to select a database.
  - c. In the Locate Database Files dialog box, navigate to the location of the database, and select

the appropriate .mdf file.

- d. Click **OK** to accept the database selection.
- e. If the location of the .ldf file is in a different folder, click the ellipsis button (...) in the database details section for the .ldf file for the database, and then select the appropriate .ldf file.
- f. Click **OK**.

You have attached the selected database. Repeat this step for each database that you need to attach.

5. Verify that this procedure restored your databases

You cannot verify that the information in the database is correct and accounted for, but you can verify that the tables exist and contain appropriate information. To ensure the tables exist and contain the appropriate information, run the following queries, and then verify that each query displays information.

```
PRINT 'Number of active accounts on server'  
SELECT COUNT(*) FROM Registry.dbo.Customer  
WHERE Status = 'A'  
PRINT 'Number of ArchiveSet rows on server'  
SELECT COUNT(*) FROM Directory.dbo.ArchiveSet
```

The results of the first query returns the number of active accounts in your SQL database. If that number does not match the number of active accounts that you believe are in your SQL database, contact Support.

## Install the Data Center Software

This section describes how to install the Data Center software on a primary Data Center server where data on both sides of the mirrored pair was lost or corrupted because of a disaster.

### To install the Data Center Software on the primary server after a disaster

1. From your backup, copy the .reg file that you created in [Before You Begin, on page 7](#) to the Data Center in recovery, and then run the file to import the Master Encryption Keys (MEK and PMEK).
2. Install the Connected Backup Data Center software as the Primary server in an existing cluster. For more information, refer to the *Installing the Data Center* guide.
3. On the server in recovery, use the DCMC to stop all Data Center services.
4. From your backup, copy the following files to \DataCenter:
  - PrivateKey.pem
  - Certificate.pem
  - dh1024.pem
  - License.dat
5. From your backup, copy the Configuration\$ folder to \DataCenter.
6. From your backup of the Configuration\$ folder, copy the cafile.pem file to the DataCenter\ folder.

7. On the server in recovery, use the DCMC to re-start all Data Center services.  
You have installed the Data Center software.

## Verify the Data Center Recovery

### To verify recovery of the Data Center

1. To verify that the Support Center works, log on and search for a number of accounts.
2. To verify that Account Management Website works, log on and view account information (if applicable).

Some database processes might take place after the database backup but before the actual disaster, which are no longer accounted for in the database. The following is a partial list of items that might not appear in the database:

- Accounts registered during that time
- Backups for current accounts
- Changes made to account status
- New Support Center technicians created
- Support Center technician password changed

## Recover the Secondary Server

After you recover the primary Data Center server affected by a disaster, recover the secondary Data Center server. To recover the secondary server in the mirrored pair, perform the procedures in [Recover One Data Center Server of a Mirrored Pair, on page 15](#).

# Chapter 4: Recovering a Clustered Data Center

This chapter describes how to recover a clustered Data Center.

- [Recover a Clustered Data Center Server, below](#)
- [Recover a Mirrored Pair from a Clustered Data Center, on page 29](#)
- [Recover a Non-Mirrored Clustered Data Center, on page 30](#)

## Recover a Clustered Data Center Server

This section describes how to recover one Data Center in a server pair in a clustered Data Center configuration.

If you need to recover more than one server in the cluster, as long as the other server in their pair still functions, use this section for each affected server.

## Tasks

To recover one Data Center server of a pair of servers in a cluster, complete the following tasks:

### NOTE:

You must complete the following tasks in order. If you have already completed tasks during your recovery, continue with the task that contains the next steps for the disaster recovery.

1. Before you perform the procedures in this manual, make sure you have the required files and information for the disaster recovery. See [Before You Begin, on page 7](#).
2. Install the operating system. See [Install and Configure Microsoft Windows, below](#)
3. Install SQL Server. See [Install and Configure SQL Server, on the next page](#)
4. Restore the SQL databases. See [Recover Databases to a Data Center Server, on the next page](#).
5. Install the Data Center software. See [Install the Data Center Software, on page 26](#).
6. Change the volume IDs of the archives. See [Change the Volume IDs for Archives, on page 27](#).
7. Find and remove orphaned archives. See [Find and Remove Orphaned Archives, on page 27](#).
8. Verify the recovered Data Center. See [Verify the Data Center Recovery, on page 28](#)

## Install and Configure Microsoft Windows

To install the Microsoft Server operating system, use the following guidelines:

- Use the same software version that you installed on the Data Center server before the disaster.
- For information about how to install the Microsoft Server operating system, refer to Chapter 2: Preparing for Installation in the *Installing the Data Center* guide.
- For information about Data Center hardware and software requirements, refer to the *Connected Backup Requirements Matrix* guide.

## Install and Configure SQL Server

To install SQL Server, use the following guidelines:

- Use the same software version that you installed on the Data Center server before the disaster.
- Use the same domain account that you previously used for your Data Center installation.

**CAUTION:**

Ensure that the Data Center installation account has local administrator privileges and SQL Server sa account rights.

If you attempt a Data Center recovery with an account that does not have SQL Server sa account rights, you will have to reinstall SQL Server and restart the Data Center recovery.

- For information about how to install SQL Server, refer to Chapter 2: Preparing for Installation in the *Installing the Data Center* guide.

## Recover Databases to a Data Center Server

This section explains how to restore the Data Center databases from one side of the Data Center pair to the other after database loss on the recovering server. This procedure enables backups and restorations to continue on the functional server.

### To restore your databases from a working Data Center server in a pair to the Data Center server in recovery

1. On the functional server, use the DCMC to stop all Data Center services.
2. Copy the appropriate files from the functional server to the server in recovery:
  - Directory.bak
  - Registry.bak

**NOTE:**

Depending on the role of the Data Center pair, the functional server might have only a Directory.bak file, as it could be a directory server in the cluster. Registration Master servers will have a Registry.bak file, and could also have a Directory.bak file if the pair is not a dedicated Registration Master pair of servers

By default, these files are located in \Program Files\Microsoft SQL Server\MSSQL\Backup on the designated SQL database volume. You select this volume during the Data Center Setup process.

3. On the server in recovery, use the Services Control Panel to stop the SQL Server and SQL Server Agent services. Then, restart the SQL Server and SQL Server Agent services (in that order). This restart ensures that no connections that can prevent recovery exist between the databases.
4. On the server in recovery, run the database\_recovery.sql script from \DataCenter\DRProcs on the functional server to restore the database backups.

If the backup and database files are not in the default locations, using Notepad, edit the database\_recovery.sql script to replace \Program Files\Microsoft SQL Server\MSSQL with the correct location of the backup and database files

5. Make sure that your SQL service account has read access to the volumes that contain the Customer archives.
6. On the server in recovery, run the `FilesInCustomersFolder.sql` script from `\DataCenter\DRProcs` on the functional server. This process consumes more time and does not display any status.

7. Run the following query:

```
EXEC Directory..sp_UpdateVolumeID
```

8. On both servers, to verify that you recovered the databases correctly, run the following queries:

```
SELECT COUNT(*) 'Customer Rows' FROM RegistryMaster.Registry.dbo.Customer  
SELECT COUNT(*) 'Community Rows' FROM RegistryMaster.Registry.dbo.Community  
SELECT COUNT(*) 'ArchiveSet Rows' FROM Directory.dbo.ArchiveSet  
SELECT COUNT(*) 'Symlink Rows' FROM Directory.dbo.Symlink
```

All counts should be equal or close to equal on both sides of the mirrored pair.

These queries let you verify that the tables exist and contain appropriate information.

9. On both servers, close the SQL Server Management Studio.
10. On the functional server, use the DCMC to restart the `ReplicationServer` and `Compactor` services.

## Install the Data Center Software

This section describes how to install the Data Center software on a Data Center server on which data was lost or corrupted because of a disaster.

### To install the Data Center Software after a disaster

1. From your backup, copy the `.reg` file that you created in [Before You Begin, on page 7](#) to the Data Center in recovery, and then run the file to import the Master Encryption Keys (MEK and PMEK).
2. Install the Connected Backup Data Center software in the same role you initially installed it.
  - If your server in recovery was the primary Registration Master server in the cluster, install the Data Center software as the **Primary server in a new cluster**.
  - If your server in recovery was a directory server on the primary side of the cluster, install the Data Center software as the **Primary server in an existing cluster**.
  - If your server in recovery was a server on the secondary side of the cluster (Registration Master or directory), install the Data Center software as the **Secondary server**.

Use the same Server ID and Server Group ID values that were in use before the disaster. For more information, refer to the *Installing the Data Center* guide.

3. On the server in recovery, open the DCMC, and then stop all the Data Center services.
4. From your backup, copy the following files to `\DataCenter`:
  - `PrivateKey.pem`
  - `Certificate.pem`

- dh1024.pem
  - License.dat
5. From your backup, copy the Configuration\$ folder to \DataCenter.
  6. From your backup of the Configuration\$ folder, copy the cafile.pem file to the DataCenter\ folder.
  7. On the server in recovery, use the DCMC to restart all Data Center services.  
You have installed the Data Center software.

## Change the Volume IDs for Archives

If the server in recovery is a secondary Data Center server, change the volume IDs of the archives for Data Copier to function.

This procedure depends on whether your Data Center servers store archives on a single volume or multiple volumes.

### To change the volume IDs for archives

1. If your Data Center servers are configured with a single archive storage volume, use SQL Server Management Studio on the server in recovery to run the following SQL query:  

```
SELECT ID FROM Directory.dbo.Volumes  
WHERE ServerID = <server>
```

where  
<server> is the Server ID for the server in recovery.
2. To point the archives to the volume ID on the server in recovery, run the following SQL query:  

```
UPDATE Directory.dbo.ArchiveSet  
SET VolumeID = <id>
```

where  
<id> is the volume ID returned from step 1.
3. If your Data Center servers are configured with multiple archive storage volumes, run the following SQL query on the server in recovery:  

```
UPDATE Directory.dbo.ArchiveSet  
SET VolumeID = -1
```

This script changes the archive references on the server in recovery to show that they are not located on the server. To associate archives with their correct volume locations, see [Find and Remove Orphaned Archives, below](#).

## Find and Remove Orphaned Archives

Restoring the databases might leave some newly backed up archives orphaned on the Data Center server.

When an Agent performs a backup that puts archives on the Data Center, the Data Center tracks these files in the Directory database. If an Agent sends archives to the Data Center after the last good

backup of the Directory database, the restored database no longer has information about the archives. This creates orphaned archives.

### To find orphaned archives on a Data Center server and remove them

1. On the server in recovery, use the DCMC to stop all Data Center services.
2. On the server in recovery, open the SQL Server Management Studio, and then connect to the server in recovery. Make sure you use an account with administrative privileges. You cannot perform this procedure remotely using SQL Server Management Studio.
3. Run the `FilesInCustomersFolder.sql` script from `\DataCenter\DRProcs`. This process consumes more time and does not display any status.
4. Make sure that no errors occurred. If you see errors in the script results, contact Support.
5. Run the following query:

```
EXEC Directory..sp_ListUnregisteredFilesInCustomersFolder 'C:\Archives_Orphaned\RemoveFiles.txt'
```

This command creates a text file that lists archives and files that are on disk, but not indexed in the database.

6. Review the text file for accuracy. If you are unsure the status of a file, copy the file to a new location or remove the entry from the list.

**NOTE:** Files referenced in `RemoveFiles.txt` will be deleted by the process unless you remove the file names from `RemoveFiles.txt`.

7. After you review the file, rename `RemoveFiles.txt` as `RemoveFiles.bat`.
8. Use Windows Explorer or the Command Prompt window to run `RemoveFiles.bat` to delete the referenced files from the Data Center.
9. In SQL Server Management Studio, enter the following command:  

```
EXEC Directory..sp_FilesInCustomersFolderCleanup
```

This command removes the database items that the stored procedures in this process created and used.
10. On the server in recovery, close the SQL Server Management Studio.
11. On the server in recovery, use the DCMC to restart all Data Center services.

## Verify the Data Center Recovery

### To verify recovery of the Data Center

1. To verify that the Support Center works, log on and search for a number of accounts.
2. To verify that Account Management Website works, log on and view account information (if applicable).

Some database processes might take place after the database backup but before the actual disaster, which are no longer accounted for in the database. The following is a partial list of items that might not appear in the database:

- Accounts registered during that time
- Backups for current accounts

- Changes made to account status
- New Support Center technicians created
- Support Center technician password changed

## Recover a Mirrored Pair from a Clustered Data Center

This section contains procedures that explain how to recover both servers of a mirrored pair in a clustered Data Center environment.

### Tasks

To recover both servers of a mirrored pair within a clustered Data Center, complete following steps:

**NOTE:**

You must complete the following tasks in order. If you have already completed tasks during your recovery, continue with the task that contains the next steps for the disaster recovery.

1. Before you start any of the procedures in this manual. See [Before You Begin, on page 7](#).
2. Install the operating system. See [Install and Configure Microsoft Windows, on page 24](#).
3. Install SQL Server. See [Install and Configure SQL Server, on page 25](#)
4. Restore the SQL databases. See [Recover Databases to a Data Center Server, on page 25](#)
5. Install the Data Center software. See [Install the Data Center Software, on page 26](#)
6. Recover the archives. See [Recover the Archives After a Disaster, on the next page](#).
7. Verifications. See [Verify the Data Center Recovery, on the previous page](#).

### Restrictions

Use this procedure whether the pair lost was a Registration Master pair or a directory pair. If all servers in the cluster were lost, use this procedure to recover the Registration Master servers first and then each directory server pair next. This procedure assumes that a good and recent database backup and the archives are available.

Contact Support if the following scenarios have occurred:

- You have lost the archives on your Registration Master servers.
- You have lost the SQL databases on your Registration Master servers and a good, recent backup of the databases is not available.

Use the [Recover a Clustered Data Center Server, on page 24](#) if only one server of the mirror has been lost to a disaster.

## Recover the Archives After a Disaster

### To recover the archives

1. In the DataCopier - Select Option window, select **Recover a volume**, and then click **Next**.
2. In the DataCopier - Select Volume window, select the volume to be recovered, and then click **Next**.
3. In the DataCopier - Summary window, click **Next**, and then click **Start**.

The time required for the recovery process to complete for all the archives that you need to recover can take hours or days. It is important to monitor the status of the archive recovery process.

4. To monitor the progress of the archive recovery
  - a. Open the DataCopier Status window.
  - b. To view the DataCopier log, click **Show Log**.
  - c. To refresh the log, close the file and then click **Show Log** again.

If DataCopier could not recover certain archives, Compactor removes the references to the missing archives and then sends a notification to the accounts to back up another copy of the file. Therefore, it is important to run Compactor service after the recovery process completes.

5. Compact any accounts that have a large number of missing archives.
6. Use Data Center Management Console to verify that backups and restores are allowed. For detailed instructions, refer to the Data Center Management Console Help.

## Recover a Non-Mirrored Clustered Data Center

This section describes how to recover your Registry Master Server and Directory Server in a Non-Mirrored Clustered Data Center configuration.

### Tasks

To restore a Non-Mirrored Clustered Data Center, perform the following tasks in the order that they are presented:

#### **NOTE:**

You must complete the following tasks in order. If you have already completed tasks during your recovery, continue with the task that contains the next steps for the disaster recovery.

1. Before you perform the procedures in this manual, ensure you have the required files and information for the disaster recovery. See [Before You Begin, on page 7](#).
2. Install the Microsoft Windows Server operating system. See [Install and Configure Microsoft Windows, on the next page](#).
3. Install Microsoft SQL Server. See [Install and Configure SQL Server, on the next page](#).
4. Restore the SQL databases. See [Recover the Connected Databases, on the next page](#).
5. Install the Data Center software. See [Install the Data Center Software, on page 33](#).
6. Verify that the procedures have restored your Data Center components. See [Data Center Verifications, on page 33](#).

## Restrictions

Use this procedure whether the server lost was a Registry Master Server or a Directory Server. If all servers in the cluster were lost, use this procedure to recover the Registry Master Server first and then subsequent Directory Server. This procedure assumes that a good and recent database backup and the archives are available.

Contact Support if the following scenarios have occurred:

- You have lost the archives on your Registry Master Server.
- You have lost the SQL databases on your Registry Master Server and a good, recent backup of the databases is not available.

## Install and Configure Microsoft Windows

To install the Microsoft Server operating system, use the following guidelines:

- Use the same software version that you installed on the Data Center server before the disaster.
- For information about how to install the Microsoft Server operating system, refer to Chapter 2: Preparing for Installation in the *Installing the Data Center* guide.
- For information about Data Center hardware and software requirements, refer to the *Connected Backup Requirements Matrix* guide.

## Install and Configure SQL Server

To install SQL Server, use the following guidelines:

- Use the same software version that you installed on the Data Center server before the disaster.
- Use the same domain account that you previously used for your Data Center installation.

### CAUTION:

Ensure that the Data Center installation account has local administrator privileges and SQL Server sa account rights.

If you attempt a Data Center recovery with an account that does not have SQL Server sa account rights, you will have to reinstall SQL Server and restart the Data Center recovery.

- For information about how to install SQL Server, refer to the Chapter 2: Preparing for Installation in the *Installing the Data Center* guide.

## Recover the Connected Databases

If the Data Center databases have been lost or corrupted during the server disaster, use the following procedure to restore the Registry and Directory databases to the Data Center server. Perform this task on each database that you need to restore.

### To restore the databases

1. From your backup, copy the .bak or .mdf and the .ldf files to the same folder location on the Data Center in recovery as was on the original Data Center.

**NOTE:**

You must restore both Registry and Directory databases for a Registry Master Server, and for a Directory Server you must restore just a Directory database.

2. Open the SQL Server Management Studio and then connect to the Data Center server in recovery.
3. If you restore databases from a backup (.bak files)
  - a. Right-click **Databases**, and then click **Restore Database**.
  - b. Type the name of the database to restore in **To database**.
  - c. Select **From device**, and then click the ellipsis button (...).
  - d. Ensure that **File** is selected for **Backup Media**, and then click **Add**.
  - e. Navigate to the location of the .bak file and select the file. Click **OK**.
  - f. To start the database restore process, click **OK**.

You have restored the selected database. Repeat this step for each database you need to restore.

4. If you restore databases from backed up .mdf and .ldf files
  - a. Right-click **Databases** and then click **Attach**. The Attach Databases dialog box opens.
  - b. Click **Add** to select a database. The Locate Database Files dialog box opens.
  - c. Navigate to the location of the database and select the appropriate .mdf file.
  - d. Click **OK** to accept the database selection.
  - e. If the location of the .ldf file is in a different folder, click the ellipsis button (...) in the database details section for the .ldf file for the database, and then select the appropriate .ldf file.
  - f. Click **OK**.

You have attached the selected database. Repeat this step for each database that you need to attach.

- g. Verify that this procedure restored your databases.

You cannot verify that the information in the database is correct and accounted for, but you can verify that the tables exist and contain appropriate information. To ensure the tables exist and contain the appropriate information, run the following queries, and then verify that each query displays information.

```
PRINT 'Number of active accounts on server'  
SELECT COUNT(*) FROM Registry.dbo.Customer  
WHERE Status = 'A'  
PRINT 'Number of ArchiveSet rows on server'  
SELECT COUNT(*) FROM Directory.dbo.ArchiveSet
```

**NOTE:**

You must run the SQL query for a registry database only on a Registry Master Server, and not on a Directory Server.

The results of the first query returns the number of active accounts in your SQL database. If that number does not match the number of active accounts that you believe are in your SQL database, contact Support

## Install the Data Center Software

Use the following procedure to install the Data Center software on a Registry Master Server or Directory Server that was lost or corrupted.

### To install the Data Center Software after a disaster

1. From your backup, copy the .reg file that you created in [Before You Begin, on page 7](#) to the Data Center in recovery, and then run the file to import the Master Encryption Keys (MEK and PMEK).
2. Install the Connected Backup Data Center software on one of the following servers on which the data was lost or corrupted because of a disaster:
  - If your server in recovery was a Registry Master Server in the non-mirrored cluster, install the Data Center software as a **Standalone Server**.
  - If your server in recovery was a Directory Server in the non-mirrored cluster, install the Data Center software as a **Primary Server in an existing cluster**, and select **Non-Mirrored Directory Server** checkbox.

For more information, refer to the *Installing the Data Center* guide.

3. Open the Data Center Management Console (DCMC), and then stop all Data Center services.
4. From your backup, copy the following files to \DataCenter:
  - PrivateKey.pem
  - Certificate.pem
  - dh1024.pem
  - License.dat
5. From your backup, copy the Configuration\$ folder to \DataCenter.
6. From your backup of the Configuration\$ folder, copy the cafile.pem file to the DataCenter\ folder.
7. Use the DCMC to restart Data Center services.  
You have installed the Data Center software.

## Data Center Verifications

### To verify that you have recovered the Data Center

1. To verify that the Support Center works, log on and search for any number of accounts.
2. To verify that Account Management Website works, log on and view account information (if applicable).

You might be unable to account for some database processes because they might happen after the database backup occurs, but before the actual disaster. The following list includes some items that might not appear in the database:

- Accounts registered after the last backup
- Backups for current accounts

- Changes made to account status
- New Support Center technicians created
- Support Center technician password changed

## Send documentation feedback

If you have comments about this document, you can [contact the documentation team](#) by email. If an email client is configured on this system, click the link above and an email window opens with the following information in the subject line:

**Feedback on Data Center Disaster Recovery (HPE Connected Backup 8.8.7)**

Add your feedback to the email and click **Send**.

If no email client is available, copy the information above to a new message in a web mail client, and send your feedback to [AutonomyTPFeedback@hpe.com](mailto:AutonomyTPFeedback@hpe.com).

We appreciate your feedback!